

Food Grade Compliance Documentation

PRODUCT: CRC FOOD GRADE PENETRATING OIL

CODE: FG03086

SIZE: 312g

THIS DOCUMENT CONTAINS

SDS

TDS

- NSF Registration
- Allergen Certificate
- HACCP Certification



IN CASE OF EMERGENCY CALL: 13 11 26

CRC Industries Australia Pty. Ltd.

9 Gladstone Road Castle Hill NSW 2154, Australia www.crcindustries.com.au

Toll Free: 1800 224 227

Email: info.au@crcind.com



The Professional's Choice

SAFETY DATA SHEET

1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

1.1 Product identifier

Product name FOOD GRADE PENETRATING OIL (FG03086)

Synonyms FG03086 - PRODUCT CODE

1.2 Uses and uses advised against

Uses LUBRICANT • LUBRICANT - AEROSOL

1.3 Details of the supplier of the product

Supplier name CRC INDUSTRIES (AUST) PTY LIMITED

Address 9 Gladstone Road, Castle Hill, NSW, 2154, AUSTRALIA

 Telephone
 (02) 9849 6700

 Fax
 (02) 9680 4914

 Email
 info.au@crcind.com

 Website
 www.crcindustries.com.au

1.4 Emergency telephone numbers

Emergency 13 11 26 (PIC)

2. HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

CLASSIFIED AS HAZARDOUS ACCORDING TO SAFE WORK AUSTRALIA CRITERIA

Physical Hazards

Aerosols - Flammable: Category 2 Aerosols - Pressurised: Category 2

Health Hazards

Aspiration Hazard: Category 1 Skin Corrosion/Irritation: Category 2

Specific Target Organ Toxicity (Single Exposure): Category 3 (Narcotic Effects)

Environmental Hazards

Not classified as an Environmental Hazard

2.2 GHS Label elements

Signal word DANGER

Pictograms







Hazard statements

H223 Flammable aerosol.

H229 Pressurized container: may burst if heated.
H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.



PRODUCT NAME FOOD GRADE PENETRATING OIL (FG03086)

Prevention statements

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.

P211 Do not spray on an open flame or other ignition source.
P251 Pressurized container: Do not pierce or burn, even after use.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P264 Wash thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

Response statements

P301 + P310 IF SWALLOWED: Immediately call a POISON CENTRE or doctor/physician.

P302 + P352 IF ON SKIN: Wash with plenty of soap and water.

P304 + P340 IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing.

P312 Call a POISON CENTRE or doctor/physician if you feel unwell.

P321 Specific treatment is advised - see first aid instructions.

P331 Do NOT induce vomiting.

P332 + P313 If skin irritation occurs: Get medical advice/ attention.
P362 Take off contaminated clothing and wash before re-use.

Storage statements

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C.

Disposal statements

P501 Dispose of contents/container in accordance with relevant regulations.

2.3 Other hazards

No information provided.

3. COMPOSITION/ INFORMATION ON INGREDIENTS

3.1 Substances / Mixtures

Ingredient	CAS Number	EC Number	Content
DISTILLATES (PETROLEUM), HYDROTREATED LIGHT	64742-47-8	265-149-8	>60%
WHITE MINERAL OIL (PETROLEUM)	8042-47-5	232-455-8	30 to 60%
CARBON DIOXIDE	124-38-9	204-696-9	<10%

4. FIRST AID MEASURES

4.1 Description of first aid measures

Eye If in eyes, hold eyelids apart and flush continuously with running water. Continue flushing until advised to

stop by a Poisons Information Centre, a doctor, or for at least 15 minutes.

Inhalation If inhaled, remove from contaminated area. To protect rescuer, use a Type A (Organic vapour) respirator or

an Air-line respirator (in poorly ventilated areas). Apply artificial respiration if not breathing.

Skin If skin or hair contact occurs, remove contaminated clothing and flush skin and hair with running water.

Continue flushing with water until advised to stop by a Poisons Information Centre or a doctor.

Ingestion For advice, contact a Poisons Information Centre on 13 11 26 (Australia Wide) or a doctor (at once). If

swallowed, do not induce vomiting. Ingestion is considered unlikely due to product form.

First aid facilities Eye wash facilities and safety shower should be available.

4.2 Most important symptoms and effects, both acute and delayed

See Section 11 for more detailed information on health effects and symptoms.

4.3 Immediate medical attention and special treatment needed

Treat symptomatically.

5. FIRE FIGHTING MEASURES

5.1 Extinguishing media

Dry agent, carbon dioxide or foam. Prevent contamination of drains and waterways.

ChemAlert.

PRODUCT NAME FOOD GRADE PENETRATING OIL (FG03086)

5.2 Special hazards arising from the substance or mixture

Flammable aerosol. May evolve toxic gases (carbon oxides, hydrocarbons) when heated to decomposition. Aerosol may explode at temperatures exceeding 50°C. Eliminate all ignition sources, including cigarettes, open flames, spark producing switches/tools, heaters, pilot lights, mobile phones, etc when handling. Aerosol cans may explode above 50°C.

5.3 Advice for firefighters

Evacuate area and contact emergency services. Toxic gases may be evolved in a fire situation. Remain upwind and notify those downwind of hazard. Wear full protective equipment including Self Contained Breathing Apparatus (SCBA) when combating fire. Use waterfog to cool intact containers and nearby storage areas.

5.4 Hazchem code

2YE

- 2 Fine Water Spray.
- Y Risk of violent reaction or explosion. Wear full fire kit and breathing apparatus. Contain spill and run-off.
- E Evacuation of people in and around the immediate vicinity of the incident should be considered.

6. ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

Wear Personal Protective Equipment (PPE) as detailed in section 8 of the SDS. Clear area of all unprotected personnel. Ventilate area where possible.

6.2 Environmental precautions

Prevent product from entering drains and waterways.

6.3 Methods of cleaning up

Contain spillage, then cover / absorb spill with non-combustible absorbent material (vermiculite, sand, or similar), collect and place in suitable containers for disposal.

6.4 Reference to other sections

See Sections 8 and 13 for exposure controls and disposal.

7. HANDLING AND STORAGE

7.1 Precautions for safe handling

Before use carefully read the product label. Use of safe work practices are recommended to avoid eye or skin contact and inhalation. Observe good personal hygiene, including washing hands before eating. Prohibit eating, drinking and smoking in contaminated areas.

7.2 Conditions for safe storage, including any incompatibilities

Store in a cool (< 50°C), dry, well ventilated area, removed from incompatible substances, heat or ignition sources and foodstuffs. Ensure aerosol containers/ cans are adequately labelled, protected from physical damage and sealed when not in use. Check regularly for damaged/leaking containers. Large storage areas should have appropriate fire protection systems.

7.3 Specific end uses

No information provided.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

8.1 Control parameters

Exposure standards

Ingredient	Reference	T\	NA	STEL	
ingredient	I/GIGIGIICG	ppm		ppm	mg/m³
Carbon dioxide	SWA [AUS]	5000	9000	30000	54000
Carbon dioxide in coal mines	SWA [AUS]	12500	22500	30000	54000
Carbon dioxide in coal mines	SWA [Proposed]	5000	9000	30000	54000
Mineral Oil Mist	SWA [AUS]		5		

Biological limits

No biological limit values have been entered for this product.



SDS Date: 30 Jul 2020 Revision No: 2.3

Page 3 of 7

PRODUCT NAME **FOOD GRADE PENETRATING OIL (FG03086)**

8.2 Exposure controls

Engineering controls Avoid inhalation. Use in well ventilated areas. Where an inhalation risk exists, mechanical explosion proof

extraction ventilation is recommended. Flammable vapours may accumulate in poorly ventilated or confined areas. Vapours are heavier than air and may travel some distance to an ignition source and flash back.

Maintain vapour levels below the recommended exposure standard.

PPE

Eye / Face Wear splash-proof goggles. Hands Wear nitrile or neoprene gloves.

When using large quantities or where heavy contamination is likely, wear coveralls. Body

Respiratory At high vapour levels, wear a Type A-Class P1 (Organic gases/vapours and Particulate) respirator.





9. PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

CLEAR LIQUID (AEROSOL DISPENSED) **Appearance**

ODOURLESS Odour

FLAMMABLE AEROSOL **Flammability** Flash point 70°C (liquid component) **Boiling point** 218°C (estimated) **Melting point** -58°C (estimated) **Evaporation rate** NOT AVAILABLE pН **NOT AVAILABLE**

Vapour density > 1 (Air = 1)Specific gravity 0.81

Solubility (water) **INSOLUBLE**

Vapour pressure 903.2 hPa (estimated) Upper explosion limit 5.5 % (estimated) Lower explosion limit 0.6 % (estimated) Partition coefficient NOT AVAILABLE NOT AVAILABLE Autoignition temperature **NOT AVAILABLE Decomposition temperature** NOT AVAILABLE Viscosity NOT AVAILABLE **Explosive properties NOT AVAILABLE** Oxidising properties

NOT AVAILABLE Odour threshold

9.2 Other information

% Volatiles 98.4 % (estimated)

10. STABILITY AND REACTIVITY

10.1 Reactivity

Carefully review all information provided in sections 10.2 to 10.6.

10.2 Chemical stability

Stable under recommended conditions of storage.

10.3 Possibility of hazardous reactions

Polymerization is not expected to occur.

10.4 Conditions to avoid

Avoid heat, sparks, open flames and other ignition sources.

10.5 Incompatible materials

Incompatible with oxidising agents (e.g. hypochlorites), acids (e.g. nitric acid), alkalis (e.g. sodium hydroxide), heat and ignition sources.

ChemAlert.

PRODUCT NAME **FOOD GRADE PENETRATING OIL (FG03086)**

10.6 Hazardous decomposition products

May evolve toxic gases (carbon oxides, hydrocarbons) when heated to decomposition.

11. TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

Acute exposure may result in nausea, vomiting, abdominal pain, diarrhoea, dizziness and drowsiness. This Acute toxicity

product may have the potential to cause adverse health effects if intentionally misused (e.g. deliberately

inhaling contents).

Information available for the ingredients:

Ingredient	Oral LD50	Dermal LD50	Inhalation LC50
DISTILLATES (PETROLEUM), HYDROTREATED LIGHT	> 2000 mg/kg (rat)	> 2000 mg/kg (rabbit)	
WHITE MINERAL OIL (PETROLEUM)	> 5000 mg/kg (rat)	> 2000 mg/kg (rabbit)	5 mg/L/4hrs (rat)

Skin Contact may result in drying and defatting of the skin, rash and dermatitis.

Eye Contact may result in irritation, lacrimation and redness. Sensitisation Not classified as causing skin or respiratory sensitisation.

Not classified as a mutagen. Mutagenicity Carcinogenicity Not classified as a carcinogen. Reproductive Not classified as a reproductive toxin.

STOT - single Over exposure may result in irritation of the nose and throat, coughing and headache. High level exposure

exposure may result in nausea, dizziness and drowsiness.

Not classified as causing organ damage from repeated exposure. STOT - repeated

exposure

Ingestion is considered unlikely due to product form. However, if liquid component is ingested, aspiration into **Aspiration**

the lungs may cause chemical pneumonitis and pulmonary oedema.

12. ECOLOGICAL INFORMATION

12.1 Toxicity

No data available.

12.2 Persistence and degradability

No data is available on the degradability of this product.

12.3 Bioaccumulative potential

No data available.

12.4 Mobility in soil

No data available.

12.5 Other adverse effects

No information provided.

13. DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods

Waste disposal For small amounts, absorb contents with sand or similar and dispose of to an approved landfill site. Do not

puncture or incinerate aerosol cans. Contact the manufacturer/supplier for additional information (if required).

Dispose of in accordance with relevant local legislation. Legislation

14. TRANSPORT INFORMATION

CLASSIFIED AS A DANGEROUS GOOD BY THE CRITERIA OF THE ADG CODE





	LAND TRANSPORT (ADG)	SEA TRANSPORT (IMDG / IMO)	AIR TRANSPORT (IATA / ICAO)
14.1 UN Number	1950	1950	1950
14.2 Proper Shipping Name	AEROSOLS	AEROSOLS	AEROSOLS
14.3 Transport hazard class	2.1	2.1	2.1
14.4 Packing Group	None allocated.	None allocated.	None allocated.

14.5 Environmental hazards

Not a Marine Pollutant.

14.6 Special precautions for user

 Hazchem code
 2YE

 GTEPG
 2D1

 EmS
 F-D, S-U

15. REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Poison schedule A poison schedule number has not been allocated to this product using the criteria in the Standard for the

Uniform Scheduling of Medicines and Poisons (SUSMP).

Classifications Safework Australia criteria is based on the Globally Harmonised System (GHS) of Classification and

Labelling of Chemicals.

Inventory listings AUSTRALIA: AllC (Australian Inventory of Industrial Chemicals)

All components are listed on AIIC, or are exempt.

16. OTHER INFORMATION

Additional information

AEROSOL CANS may explode at temperatures approaching 50°C.

RESPIRATORS: In general the use of respirators should be limited and engineering controls employed to avoid exposure. If respiratory equipment must be worn ensure correct respirator selection and training is undertaken. Remember that some respirators may be extremely uncomfortable when used for long periods. The use of air powered or air supplied respirators should be considered where prolonged or repeated use is necessary.

PERSONAL PROTECTIVE EQUIPMENT GUIDELINES:

The recommendation for protective equipment contained within this report is provided as a guide only. Factors such as form of product, method of application, working environment, quantity used, product concentration and the availability of engineering controls should be considered before final selection of personal protective equipment is made.

HEALTH EFFECTS FROM EXPOSURE:

It should be noted that the effects from exposure to this product will depend on several factors including: form of product; frequency and duration of use; quantity used; effectiveness of control measures; protective equipment used and method of application. Given that it is impractical to prepare a report which would encompass all possible scenarios, it is anticipated that users will assess the risks and apply control methods where appropriate.



PRODUCT NAME FOOD GRADE PENETRATING OIL (FG03086)

Abbreviations ACGIH American Conference of Governmental Industrial Hygienists

CAS # Chemical Abstract Service number - used to uniquely identify chemical compounds

CNS Central Nervous System

EC No. EC No - European Community Number

EMS Emergency Schedules (Emergency Procedures for Ships Carrying Dangerous

Goods)

GHS Globally Harmonized System

GTEPG Group Text Emergency Procedure Guide
IARC International Agency for Research on Cancer

LC50 Lethal Concentration, 50% / Median Lethal Concentration

LD50 Lethal Dose, 50% / Median Lethal Dose

mg/m³ Milligrams per Cubic Metre
OEL Occupational Exposure Limit

pH relates to hydrogen ion concentration using a scale of 0 (high acidic) to 14 (highly

alkaline).

ppm Parts Per Million

STEL Short-Term Exposure Limit

STOT-RE Specific target organ toxicity (repeated exposure)
STOT-SE Specific target organ toxicity (single exposure)

SUSMP Standard for the Uniform Scheduling of Medicines and Poisons

SWA Safe Work Australia
TLV Threshold Limit Value
TWA Time Weighted Average

Report status

This document has been compiled by RMT on behalf of the manufacturer, importer or supplier of the product and serves as their Safety Data Sheet ('SDS').

It is based on information concerning the product which has been provided to RMT by the manufacturer, importer or supplier or obtained from third party sources and is believed to represent the current state of knowledge as to the appropriate safety and handling precautions for the product at the time of issue. Further clarification regarding any aspect of the product should be obtained directly from the manufacturer, importer or supplier.

While RMT has taken all due care to include accurate and up-to-date information in this SDS, it does not provide any warranty as to accuracy or completeness. As far as lawfully possible, RMT accepts no liability for any loss, injury or damage (including consequential loss) which may be suffered or incurred by any person as a consequence of their reliance on the information contained in this SDS.

Prepared by

Risk Management Technologies 5 Ventnor Ave, West Perth Western Australia 6005 Phone: +61 8 9322 1711 Fax: +61 8 9322 1794 Email: info@rmt.com.au Web: www.rmtglobal.com

[End of SDS]



SDS Date: 30 Jul 2020 Revision No: 2.3

Page 7 of 7

TECHNICAL DATA SHEET



CRC Industries (Aust) Pty. Limited

PO Box 199, Castle Hill, NSW 1765.

I. Product Description

CRC Food Grade Penetrating Oil is an industrial strength, low viscosity penetrant designed to quickly loosen and free seized, bound or frozen fasteners on all food processing equipment. The low surface tension formula creeps into cracks, seams, threads and joints with great efficiency and loosens rusted and corroded nuts, bolts, couplings, fittings, hinges and frozen components. Eases the disassembly of plant machinery, tools and equipment for routine maintenance and emergency repairs and leaves a thin non-drying colourless film with outstanding lubrication and corrosion inhibiting properties. Safe on most painted surfaces, coatings, plastics and rubbers.

Temperature range from -20 °C to 150 °C (continuous), 170 °C (intermittent). NSF H1 Registered for incidental food contact.

II. Features & Benefits

- **Eases disassembly of mechancial equipment** Low surface tension formula creeps into cracks, seams, threads and joints with great efficiency
- Improves Performance and Operating Efficiency Loosens rusted and corroded nuts, bolts, couplings, fittings, hinges and frozen components
- Corrosion inhibiting Lubricating residue prevents further corrosion
- **Non silicone** Will not harm paint, plastic or wood surfaces. Easier clean-up and removal of excess oil. Allows treated surfaces to be repainted
- High Flash Point Provides increased user safety
- 360 °C degree valve Aerosol can be sprayed from any position even upside down
- Non-toxic, colourless, odourless, tasteless
- **Temperature Range** Effective from -20 °C to 150 °C (continuous), 170 °C (intermittent)
- NSF H1 Registered for incidental food contact

III. Application and Directions

- 1. Do not use on energized systems.
- 2. Hold can 200mm to 300mm away from surface to be sprayed.
- 3. Spray a light, even film on area to be lubricated.
- 4. Wipe off excess with cloth.
- 5. Repeat application when necessary

IV. Typical Properties and Characteristics Physical Properties:

Flash Point	>+90℃ (TCC)		
Boiling Point	+215℃ Initial		
Odour	None		
Appearance	Colourless liquid		
Vapour Density	> air		
Solubility	Neg. in water		
% Volatile	65%		
Specific Gravity	0.815		

Viscosity	38-41 cST @ 40℃
Propellant	Carbon Dioxide

Performance Characteristics:

Type of film	Thin, oily film		
Dry Time	Non-drying wet oil		
Temperature Range	-20 °C to +150 °C (continuous), +170 °C (intermittent)		

V. Package Description

Part Number Size

FG03086 312grm

VI. Special Precautions

General:

Use with adequate ventilation. Store in a cool, well-ventilated area. Dispose of empty containers safely. All unused product should be disposed of in conformance with local and HSNO regulations, do not contaminate water supply.

Aerosol Cans:

Do not puncture, incinerate or store above 50 °C. Exposure to high temperatures may cause can to burst. Do not place in direct sunlight or near any heat source. Aerosol cans will conduct electricity. Keep away from all live electrical sources including battery terminals, solenoids, electrical panels and other electronic components. Failure to observe this warning may result in serious injury from flash fire and/or electrical shock.

First Aid:

Swallowed – Not considered a normal route of entry.

Skin – Remove contaminated clothing and wash skin thoroughly with soap and water. Remove any adhering solids with industrial skin cleansing cream. Do not use solvents. Seek medical attention in the event of irritation. Wash contaminated clothing before reuse.

Eyes – Immediately hold the eyelids apart and flush the eye continuously for at least 15 minutes with fresh running water.

Inhaled – Remove to fresh air. Lay patient down. Keep warm and rested.

Refer to Safety Data Sheet for more details.

PRODUCT WARRANTY: CRC offers a conditional warranty on this product for the period of 5 years from the date of manufacture.

<u>DISCLAIMER</u>: All information on this data sheet is based on testing by CRC Industries (Aust.) Pty. Ltd. All products should be tested for suitability on a particular application prior to actual use. CRC Industries (Aust.) Pty. Ltd. makes no representations or warranties of any kind concerning this data.



June 13, 2003

Steven S. Katz CRC INDUSTRIES, INC. 885 LOUIS DRIVE WARMINSTER, PA 18974 UNITED STATES

RE: CRC® Industrial Food Grade Penetrating Oil - Aerosol

Category Code: H1

NSF Registration No. 130546

Dear Steven S. Katz:

NSF has processed the application for Registration of **CRC® Industrial Food Grade Penetrating Oil - Aerosol** to *the NSF Registration Guidelines for Proprietary Substances and Nonfood Compounds* (2003), which are available at www.nsf.org/usda. The NSF Nonfood Compounds Registration Program is a continuation of the USDA product approval and listing program, which is based on meeting regulatory requirements including FDA 21 CFR for appropriate use, ingredient and labeling.

This product is acceptable as a lubricant with incidental food contact (H1) for use in and around food processing areas. Such compounds may be used on food processing equipment as a protective anti-rust film, as a release agent on gaskets or seals of tank closures, and as a lubricant for machine parts and equipment in locations in which there is a potential exposure of the lubricated part to food. The amount used should be the minimum required to accomplish the desired technical effect on the equipment. If used as an anti-rust film, the compound must be removed from the equipment surface by washing or wiping, as required to leave the surface effectively free of any substance which could be transferred to food being processed.

NSF Registration of this product is current when the NSF Registration Number, Category Code, and Registration Mark appear on the NSF-approved product label, and the registered product name is included in the current NSF White Book Listing of Nonfood Compounds at the NSF website (http://www.nsf.org/usda). The NSF Registration Mark can be downloaded from the NSF website, at http://www.nsf.org/mark/download_marks.html.

NSF Listing of all registered Nonfood compounds by NSF International is not an endorsement of those compounds, or of any performance or efficacy claims made by the manufacturer.

Registration status may be verified at any time via the NSF web site, at http://www.nsf.org/usda. Changes in formulation or label, without the prior written consent of NSF, will void registration, and will supersede the on-line listing.

Sincerely,

Carmen Grindatti

NSF Nonfood Compounds Registration Program

Company No: N02027

Global Headquarters: 800 Enterprise Road, Suite 101 | Horsham, PA 19044 | 215.674.4300 **Manufacturing and R&D Center:** 885 Louis Drive | Warminster, PA 18974 | 215.674.4300

ALLERGEN CERTIFICATE

Date: 23-Mar-23

Product Name: Food Grade Penetrating Oil

Product Code: No. 03086 (Item# 1003355)

CRC has evaluated the above product against a list of internationally recognized and regulated allergens. The following information is provided to assist our customers in complying with allergen safety programs.

Allergen	Present in	Present on Same	Present in
Allergen	Product	Production Line	Facility
Dairy / Milk	□Yes / ⊠No	□Yes / ⊠No	□Yes / ⊠No
Soy	□Yes / ⊠No	⊠Yes / □No	⊠Yes / □No
Peanut	□Yes / ⊠No	□Yes / ⊠No	□Yes / ⊠No
Egg	□Yes / ⊠No	□Yes / ⊠No	□Yes / ⊠No
Tree Nut (almonds, brazil nuts, cashews, hazelnuts,	□Yes / ⊠No	□Yes / ⊠No	□Yes / ⊠No
macadamia nuts, pecans, pine nuts, pistachio nuts and walnuts)			
Sesame Seed	□Yes / ⊠No	□Yes / ⊠No	□Yes / ⊠No
Mustard Seed	□Yes / ⊠No	□Yes / ⊠No	□Yes / ⊠No
Gluten (wheat, barley, oats, rye)	□Yes / ⊠No	□Yes / ⊠No	□Yes / ⊠No
Seafood (fish, crustacean and molluscan shellfish)	□Yes / ⊠No	□Yes / ⊠No	□Yes / ⊠No
Sulfites	□Yes / ⊠No	□Yes / ⊠No	□Yes / ⊠No
Buckwheat	□Yes / ⊠No	□Yes / ⊠No	□Yes / ⊠No
Celery	□Yes / ⊠No	□Yes / ⊠No	□Yes / ⊠No
Lupin	□Yes / ⊠No	□Yes / ⊠No	□Yes / ⊠No
Bee pollen / Propolis	□Yes / ⊠No	□Yes / ⊠No	□Yes / ⊠No
Royal Jelly	□Yes / ⊠No	□Yes / ⊠No	□Yes / ⊠No
Mango	□Yes / ⊠No	□Yes / ⊠No	□Yes / ⊠No
Peach	□Yes / ⊠No	□Yes / ⊠No	□Yes / ⊠No
Pork	□Yes / ⊠No	□Yes / ⊠No	□Yes / ⊠No
Tomato	□Yes / ⊠No	□Yes / ⊠No	□Yes / ⊠No
Latex (natural rubber)	□Yes / ⊠No	□Yes / ⊠No	□Yes / ⊠No

This information is accurate to the best of CRC Industries' knowledge or obtained from sources believed by CRC to be accurate. For more information, please contact our Technical Service Dept at 800-521-3168.

CRC INDUSTRIES, INC.

Michelle Rudrick

Michelle Rudnick Global Director of Regulatory Affairs

HACCP INTERNATIONAL

eliminate the hazard - reduce the risk



This is to certify that

CRC Industries (Aust) Pty Limited

CRC Green Light Program (SSZ) - limited to the lubricant products listed below Food Zone Classification: SSZ (Splash or Spill Zone)

> (Limited to the products listed on the Certification Statement)

are certified as suitable aids to equipment maintenance operations within food facilities that operate a

HACCP based Food Safety Programme

noting the conditions of the certification statement



03 March 2023

18 March 2025

Issue Date

Expiry Date

This certificate belongs to HACCP International and must be returned upon demand. All products and services to which this certificate refers are evaluated prior to reissue

HACCP INTERNATIONAL: No. 3 Ridgewest Building, 1 Ridge Street, North Sydney, NSW 2060, Australia www.hacco-international.com



PE-747-CRC-1-R1-05

HACCP INTERNATIONAL

eliminate the hazard - reduce the risk

Certification Statement

PE-747-CRC-1-R1-05

CRC Industries (Aust) Pty Limited

Certificate Expiry Date 18 March 2025

CRC Green Light Program (SSZ) - limited to the lubricant products listed below

Food Zone Classification: SSZ (Splash or Spill Zone)

FG03035 CRC Water Based Silicone 13oz

FG03038 CRC Food Grade White Grease 10oz

FG03039 CRC Food Grade Silicone 15oz

FG03040 CRC Food Grade Silicone 10oz

FG03054 CRC Syntha-Tech Lubricant with PTFE 11oz

FG03055 CRC Food Grade Chain Lube 12oz

FG03065 CRC Food Grade Belt Dressing 10oz

FG03081 CRC Food Grade Machine Oil 11oz

FG03082 CRC Di-Electric Grease 10oz

FG03085 CRC Food Grade Di-Electric Grease 3.3oz

FG03086 CRC Food Grade Penetrating Oil 11oz

FG03139 CRC Parcel Glide Silicone Lubricant 15oz

FG3037 CRC Food Grade Industrial Silicone Grease 75ml

FGSL35600 Sta-Lube Multi-purpose Food Grade Grease 14oz

FGSL35610 CRC Synthetic Food Grade Grease 14oz

FGSL35905 Sta-Lube FG Anti-Seize & Lubricating Compound 8oz

HACCP Australia Pty Ltd certifies the Green Light Program provided by CRC Industries as a suitable aid to equipment maintenance operations within food handling and food processing facilities that operate a HACCP based Food Safety Programme.

Licence Commencement 19 March 2023

Certificate Issue Date 03 March 2023



HACCP International's evaluation and certification is strictly confined to matters of food safety or the operation of a HACCP based Food Safety Programme. Whilst all reasonable care is taken by HACCP International in its evaluation of the product(s) or services(s) described herein, HACCP International does not guarantee that every food safety risk in every application has been identified. No guarantee is offered or implied in the issuing of this statement.

Licence Agreement

CRC Industries (Aust) Pty Limited is licensed to use the HACCP International certification mark, in accordance with HACCP International's Certification Trade Mark Rules and Conditions in Region 1 (Australasia) in respect of the products listed above, for a period of 24 months from the licence commencement date CRC Industries (Aust) Pty Limited is in receipt of the HACCP International Pty Ltd Certification Trade Mark Rules and Conditions v3.0 and agrees to abide by the conditions therein.

Licensee's Signature:

178

Date: 14/03/202