



CRC Industries (Aust) Pty Ltd

I. Product Description

CRC Belt Dressing is a specialist formulation developed to minimise squeals from automotive belts. It is ideal for use on multi-ribbed, alternator, power steering and other accessory belts.

It forms a non-drying, water-resistant film that extends belt life by reducing belt tension, slipping and dirt build-up. Belts remain pliable and will not glaze or harden while squeaking noise will be reduced. Not suited for use on timing/cam belt.



II. Application and Directions

1. Spray all gripping surfaces while belt is running.
2. Spray thoroughly, but do not saturate.
3. Re-apply at regular intervals for best results.

III. Features & Benefits

- **Tacky, non-drying, water resistant film** – Minimises drive belt slippage, resists water and wash off, maintains belt flexibility, and prevents slippage.
- **Improves traction and reduces belt tension** – Relieving stress on motors, shafts and wheels for improved operating efficiency and extended belt life.
- **Designed for most belts and belt materials** – Multi-Ribbed, Alternator, Power steering & other accessory belts.
- **Includes Permastraw™ Dual-Action Spray System** - One piece actuator with two-way spray that ensures that straw stays in place.

IV. Typical Properties and Characteristics

Physical Properties:

Flash Point	-104 °C (propellant)
Odour	Odourless
Appearance	Amber Liquid
Solubility	Insoluble in water. Soluble in many organic liquids.
Propellant	Hydrocarbon

Performance Characteristics:

Type of Film	Lubricant
Temperature Range	-25 °C to +138 °C

V. Package Description

Part Number Size

1753472 350g/500ml Aerosol + Permastraw™ Dual-Action Spray

**VI. Special Precautions**

General	<ul style="list-style-type: none">• Extremely flammable aerosol.• Keep away from heat, sparks, open flames and hot surfaces.• No smoking.• Do not spray on an open flame or other ignition source.• Avoid breathing vapours.• Use only outdoors or in a well-ventilated area.• Use personal protective equipment as required.• Store in a well-ventilated place.• Dispose of empty containers safely.• All unused product should be disposed of in conformance with local and national regulations, do not contaminate water supply.
Aerosol Cans	<ul style="list-style-type: none">• Do not puncture, incinerate or store above 50 °C.• Exposure to high temperatures may cause can to burst.• Do not place in direct sunlight or near any heat source.• Keep away from all live electrical sources including battery terminals, solenoids, electrical panels and other electronic components. Failure to observe this warning may result in serious injury from flash fire and/or electrical shock.
First Aid Measures	Eye Contact If aerosols come in contact with the eyes: <ul style="list-style-type: none">• Immediately hold the eyelids apart and flush the eye continuously for at least 15 minutes with fresh running water.• Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.• Transport to hospital or doctor without delay.• Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.
	Skin Contact If solids or aerosol mists are deposited upon the skin: <ul style="list-style-type: none">• Flush skin and hair with running water (and soap if available).• Remove any adhering solids with industrial skin cleansing cream.• DO NOT use solvents.• Seek medical attention in the event of irritation.
	Inhalation If aerosols, fumes or combustion products are inhaled: <ul style="list-style-type: none">• Remove to fresh air.• Lay patient down. Keep warm and rested.• Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures.• If breathing is shallow or has stopped, ensure clear airway and apply resuscitation, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary.• Transport to hospital, or doctor.
	Ingestion <ul style="list-style-type: none">• If swallowed do NOT induce vomiting.• If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration.• Observe the patient carefully.• Never give liquid to a person showing signs of being sleepy or with reduced awareness, i.e., becoming unconscious.• Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink.• Seek medical advice.



CRC Industries (Aust) Pty Ltd

Technical Data Sheet

Belt Dressing 1753472

TECHNICAL DATA SHEET Version 05/2023

PRODUCT WARRANTY: CRC offers a conditional warranty of this product for the period of five years from the date of manufacture.

DISCLAIMER: All information on this data sheet is based on testing by CRC Industries NZ. All products should be tested for suitability on a particular application prior to actual use. CRC Industries makes no representations or warranties of any kind concerning this data.