

TECHNICAL DATA SHEET

Product No. 5016



CRC Industries (Aust) Pty Ltd

I. Product Description

CRC DISC BRAKE QUIET stops brake squeals and squeaks. CRC DISC BRAKE QUIET is an elastomeric multi-polymer compound specially formulated to dampen the vibrations that cause disc brake noises. It forms a water and high temperature resistance film that will absorb noise and quiet disc braking.

II. Applications

CRC DISC BRAKE QUIET is ideal for all types of disc brakes on cars, 4WDs, industrial machinery disc braking systems, fork lifts, tractors, farm equipment, cement trucks, etc.

III. Features & Benefits

- ❑ CRC DISC BRAKE QUIET is easy to apply
- ❑ Resists cold, hot and water wash-off and high temperature sling-off.
- ❑ CRC DISC BRAKE QUIET reduces or eliminates squeaks and squeals from the disc brakes.
- ❑ CRC DISC BRAKE QUIET is stable and long lasting.

IV. Physical Properties without propellant

Flash point	none	Odour	Sweet ethereal
Appearance	Orange red paste	Solubility	Slight in water. Negligible when dry
		Specific Gravity	1.05

V. Specification and Approvals

VI. Performance Characteristics

Type of Film	Elastomeric
Drying Time	10 minutes to set

VII. Directions

- ❑ Read all directions and warnings before using
- ❑ Switch off and de-energize before using CRC DISC BRAKE QUIET
- ❑ Shake bottle well before using
- ❑ Clean all steel brake backing plates with CRC Brakleen before applying CRC DISC BRAKE QUIET.
- ❑ Apply liberally to back steel (or gasket) of both outboard pads. Spread evenly over entire surface.
- ❑ **Do not** apply CRC DISC BRAKE QUIET to brake linings.
- ❑ Apply one applicator width strip to the back steel of each inboard pad. (See illustration on bottle).
- ❑ Allow 10 minutes to set. May be installed when tacky.
- ❑ Replace cap after use.

VIII. Disposal

Disposal requirements vary by state and local regulations. All used and unused product should be disposed of in conformance with local, state and commonwealth laws and regulations.

IX. Special Use Warnings

General

Use only in well-ventilated area. Ventilation may be improved by opening a window or door or providing mechanical assistance. Avoid continuous breathing of vapour and spray mist. Avoid contact with the skin and eyes. If ventilation is not adequate, respiratory protection should be worn. For more information regarding short term and long term exposure, review this product's Material Safety Data Sheet.

PRODUCT WARRANTY: CRC offers a conditional warranty on this product for the period of 5 years from the date of manufacture.

DISCLAIMER: All information on this data sheet is based on testing by CRC Industries (Aust) Pty Ltd. All products should be tested for suitability on a particular application prior to actual use. CRC Industries (Aust) Pty Ltd makes no representations or warranties of any kind concerning this data.