



CRC Food Grade Belt Dressing is a synthetic formulation specifically developed to meet the demand for a true food grade belt dressing. It adheres strongly to any commonly used belt material and forms a tacky, non-drying, water resistant film.

It extends belt life by improving traction and reducing belt tension, slipping and dirt or product debris build-up. Annoying squeaks and squeals will be eliminated and stress on motors, shafts and wheels will be relieved for improved operating efficiency.

Temperature range from -20°C to 176°C (continuous), 200°C (intermittent).
 NSF H1 Registered for incidental food contact.

Item Code: FG03065

Pack Size: 283g Aerosol

Features and Benefits

- **Strong adhesive qualities:** Minimises drive belt slippage, maintains belt flexibility and prevent loads from slipping on conveyor systems
- **Extends belt life:** Belts remain pliable and will not glaze or harden
- **Improves operating efficiency:** Relieves stress on motors, shafts and wheels
- **Non-drying, water-resistant film:** Resists water wash off
- **Silences squeaking noises**
- **Suitable for most belts and material:** Flat, round, V belts. Leather, rubber, canvas, fabric.
- **Not suitable for multi-V-belts**
- **Colourless:** Will not stain finished goods transported on conveyor systems
- **360° valve:** Aerosol can be sprayed from any position even upside down
- **Non-toxic, tasteless**
- **Wide Temperature range:** Effective from from -20°C to 176°C (continuous), 200°C (intermittent)
- **NSF H1 Registered for incidental food contact**

Typical Properties and Characteristics

Flash Point	< 10°C
Boiling Point	> 48°C
Odour	Solvent
Appearance	Viscous liquid
Solubility	Negligible in water
% Volatile	92.8%
Vapour Density	> Air

Type of film	Tacky, colourless, non-drying
Dry time	Non-drying
Temperature range	-20°C to +176°C (continuous), +200°C (intermittent).
Specific Gravity	0.64
Propellant	Hydrocarbon

Directions

1. Do not apply while equipment is energized.
2. Turn off equipment and stop belts before applying.
3. Spray a light, even coating on each side of belts in contact with pulleys. Use sparingly.
4. Re-apply periodically to help extend belt and pulley bearing life.

Special Precautions

General:

Extremely flammable aerosol. Keep away from naked flames, electrical appliances/lights, lighted cigarettes, etc. Do not spray on open flame or other ignition source. Use with adequate ventilation. Store in a cool, well-ventilated area. Do not eat, drink or smoke when using this product. Dispose of contents/container in accordance with relevant regulations. All unused product should be disposed of in conformance with local and hazard regulations, do not contaminate water supply.

Aerosol Cans:

Do not puncture, incinerate or store above 50°C. Exposure to high temperatures may cause can to burst. Do not place in direct sunlight or near any heat source. Aerosol cans will conduct electricity. Keep away from all live electrical sources including battery terminals, solenoids, electrical panels and other electronic components. Failure to observe this warning may result in serious injury from flash fire and/or electrical shock.

Refer to **Safety Data Sheet** for more details.

Product Warranty or Shelf Life

CRC offers a conditional warranty on this product for the period of 5 years from the date of manufacture.

Contact Information

CRC Industries (Aust) Pty Ltd
9 Gladstone Road, Castle Hill
NSW 2154, Australia

www.crcindustries.com.au
PH: 1800 224 227
Email: info.au@crcind.com

Disclaimer: All information on this data sheet is based on testing by CRC Industries (Aust) Pty Ltd. All products should be tested for suitability on a particular application prior to actual use. CRC Industries (Aust) Pty Ltd makes no representations or warranties of any kind concerning this data.

Technical Data Sheet Version 08/2024