



TECHNICAL DATA SHEET

CRC Brakleen Quick Dry



CRC Brakleen Quick Dry is a powerful, fast evaporating non-chlorinated solvent blend with superior cleaning and degreasing properties that minimise down-time.

It is formulated to quickly and safely dissolve and flush away grease, oil, brake fluid, transmission fluid, hardened deposits and other contaminants, without the need for disassembly. It safely settles and removes hazardous brake dust.

CRC Brakleen Quick Dry is non-staining, non-corrosive, leaves no residue and evaporates quickly. It stops disc brake squeal and noise caused by contaminants, eliminates clutch slippage and helps brakes last longer and perform better.

Item Code: 5088

Pack Size: 350g Aerosol

Features and Benefits

- **Super fast evaporating cleaner & degreaser:** Minimises downtime
- **High short term exposure level:** Ideal for use in confined areas or areas with poor ventilation
- **Leaves no residue:** Prevents harmful build up and eliminates rinsing or wiping
- **No disassembly required:** Saves time and reduces maintenance cost
- **Low surface tension:** Gives excellent penetration and ensures superior dissolving and degreasing properties
- **Advanced non-chlorinated and non-toxic formula**
- **Ideal for time-sensitive jobs**

Applications

Brake linings, Clutch plates, Drums, Disc brake pads, Forklifts, CV joints, Wheel bearings, Other related brake/clutch parts, Calipers, Cylinders, Workshop equipment, Tools, Mechanical & Industrial machinery

Typical Properties and Characteristics

Flash Point	<0°C
Boiling Point	55-120°C
Odour	Petroleum like
Appearance	Clear liquid
Solubility	Insoluble

% Volatile	100%
Vapour Density	3
Specific Gravity	0.72
Flammability	Extremely Flammable
Propellant	Carbon dioxide



TOGETHER, WE GET IT DONE.™

www.crcindustries.com.au



TECHNICAL DATA SHEET

CRC Brakleen Quick Dry

Directions

1. Equipment must be de-energised before cleaning.
2. Spray liberally and allow excess to run off.
3. Repeat the application if necessary. Use extension tube for hard-to-reach areas.
4. After application, re-lubricate with CRC 5-56 if necessary.
5. Fully ventilate equipment - drying thoroughly and venting before reactivating system.

Note: Use with adequate ventilation. Check plastics and rubber compatibility before use, protect from overspray if required. Avoid prolonged contact with rubber and plastics. Do not use on sensitive electronics, use one of CRC's precision cleaners for these applications.

Special Precautions

General:

Extremely flammable aerosol. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on open flame or other ignition source. Use with adequate ventilation. Store in a cool, well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection/hearing protection. Dispose of contents/container in accordance with relevant regulations.

Aerosol Cans:

Pressurized container: may burst if heated. Do not pierce or burn, even after use. Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store locked-up. Protect from sunlight. Do not expose to temperatures exceeding 50°C.

Refer to **Safety Data Sheet** for more details.

Product Warranty or Shelf Life

CRC offers a conditional warranty on this product for the period of 5 years from the date of manufacture.

Contact Information

CRC Industries (Aust) Pty Ltd
9 Gladstone Road, Castle Hill
NSW 2154, Australia

www.crcindustries.com.au
PH: 1800 224 227
Email: info.au@crcind.com

Disclaimer: All information on this data sheet is based on testing by CRC Industries (Aust) Pty Ltd. All products should be tested for suitability on a particular application prior to actual use. CRC Industries (Aust) Pty Ltd makes no representations or warranties of any kind concerning this data.

Technical Data Sheet Version 06/2026



TOGETHER, WE GET IT DONE.™

www.crcindustries.com.au